

nifty

TrackDrive

TRACK MOUNTED ACCESS PLATFORM

12m & 17m
Working heights

Superb Gradeability
Will climb very steep
inclines as high as 60% (31°)

Excellent Traction
Better grip on uneven terrain

**Fully Proportional
Hydraulic Controls**
Simple, reliable &
easy to maintain

Weight Saving Design
Lower cost transportation &
better fuel economy on site

Non-Marking Tracks
Optional rubber-free tracks
available for indoor usage

Variable Width Tracks
Access to narrow openings
improving versatility



niftylift.com



niftylift

TrackDrive

With working heights of 12.20m and 17.10m, Nifty's new **TrackDrive** platforms offer a range of capabilities to suit operator requirements. The **TD120T** is available in two versions, the standard and narrow width machines. With 60° gradeability both offer excellent traction on steep or rough terrain and the narrow version will pass through a 0.75m opening for restricted access applications. The **TD170** provides an impressive working envelope and its TrackDrive base allows it to travel over ground where even a 4WD SP platform would have difficulty finding traction.



TD170



TD120T

Weight saving designs mean that site to site transportation is more economical. The platforms are also more efficient, allowing them to work for longer while using less fuel.

Also available are rubber-free urethane tracks. Ideal for internal or clean applications, these tracks will increase the number of locations that the TrackDrives can work, greatly improving their utilisation



TD120TN

SPECIFICATIONS

	TD120TN	TD120T	TD170
Working Height	12.20m	12.20m	17.10m
Platform Height	10.20m	10.20m	15.10m
Working Outreach	6.10m	6.10m	8.70m
Slew	406°	406°	360°
Width - Travelling	0.75m - 1.15m	1.10m	1.85m
- Working	3.00m	3.55m	4.40m
Height	1.90m	1.90m	2.10m
Length	3.95m	3.95m	5.60m
Minimum Weight	1770kg*	1800kg*	3100kg*
Platform Capacity	120kg	200kg	200kg
Platform Size	0.75m x 0.65m	1.10m x 0.65m	1.10m x 0.65m
Drive Speed	1.0mph	1.0mph	1.3mph
Gradeability	60%	60%	32%
Control System	Fully proportional hydraulic		

* Weights may vary according to specification, please confirm before ordering.

Due to a policy of continuing development and improvement, Niftylift reserves the right to change any specification without notice. Please confirm exact specification before ordering.

Supplied by:

Manufacturers of trailer mounted, self propelled and vehicle mounted platforms.

NIFTYLIFT LTD
Fingle Drive
Stonebridge
Milton Keynes
MK13 0ER
England

www.niftylift.com

e.mail: info@niftylift.com

Tel.: +44 (0)1908 223456

Fax.: +44 (0)1908 312733

